

ISO 12944-5 - Antiox



Vejledende forbrugsguide til Antiox specificeret i gr/m²,
i henhold til ISO 12944-5

Husk altid at kontakte teknisk afdeling for vejledning
eller behandlingsforslag.

Produktinformation får du på www.acrymatic.dk

Consumption guide for Antiox specified in gr/m²,
according to ISO 12944-5


Always remember to contact the technical department for guidance
or treatment suggestions.

Product information is available at www.acrymatic.dk

– dokumentation får du på www.acrymatic.dk

System: Antiox

ISO 12944-5

	Paint System				Priming and Subsequent Coat(s)				TopCoat(s)				Durability			
	NDFT	MNOC	Product	Binder type	MNOC	NDFT	Product	Binder type	MNOC	NDFT	Low	Medium	High	Very high		
C2 - Low	80	1	Antiox	AY	1	80 µm / 170 gr	Unnecessary									
Medium	140	1	Antiox	AY	1	140 µm / 310 gr	Unnecessary									
High	200	2	Antiox	AY	2	200 µm / 430 gr	Unnecessary									
Very High	240	2	Antiox	AY	2	240 µm / 520 gr	Unnecessary									
C3 - Low	140	1	Antiox	AY	1	140 µm / 310 gr	Unnecessary									
Medium	200	2	Antiox	AY	2	200 µm / 430 gr	Unnecessary									
High	240	2	Antiox	AY	2	240 µm / 520 gr	Unnecessary									
Very High	300	2	Antiox	AY	2	300 µm / 650 gr	Unnecessary									
C4 - Low	200	2	Antiox	AY	2	200 µm / 430 gr	Unnecessary									
Medium	240	2	Antiox	AY	2	240 µm / 520 gr	Unnecessary									
High	300	2	Antiox	AY	2	300 µm / 650 gr	Unnecessary									
Very High	350	2	Antiox	AY	2	350 µm / 760 gr	Unnecessary									
C5 - Low	240	2	Antiox	AY	2	240 µm / 520 gr	Unnecessary									
Medium	300	2	Antiox	AY	2	300 µm / 650 gr	Unnecessary									
High	350	2	Antiox	AY	2	350 µm / 760 gr	Unnecessary									
Very High																
Contact Acrylic Coating for the right system in C5 - Very High																
AY: Acrylic paints.	MNOC: Minimum number of coats to get to NDFT.				gr: Gram.	litr: Liter.										
NDFT: Nominal dry film thickness (Total amount of paint)	Stripe coat: Depends on the project.				Durability: Years to first major maintenance											

- Der tages forbehold for trykfejl / - Reservations are made for printing errors