

ISO 12944-5 - MonoGuard



Vejledende forbrugsguide til MonoGuard specificeret i l/m²,
i henhold til ISO 12944-5

Husk altid at kontakte teknisk afdeling for vejledning
eller behandlingsforslag.

Produktinformation får du på www.acrymatic.dk

Consumption guide for MonoGuard specified in l/m²,
according to ISO 12944-5

Always remember to contact the technical department for guidance
or treatment suggestions.

Product information is available at www.acrymatic.dk

– dokumentation får du på www.acrymatic.dk

System: MonoGuard **ISO 12944-5**

	Paint System		Priming and Subsequent Coat(s)				TopCoat(s)				Durability			
	NDFT	MNOC	Product	Binder type	MNOC	NDFT	Product	Binder type	MNOC	NDFT	Low	Medium	High	Very high
C2 - Low	50	1	MonoGuard	AY	1	50 µm / 0,116 ltr	Unnecessary				■			
Medium	65	1	MonoGuard	AY	1	65 µm / 0,151 ltr	Unnecessary					■		
High	80	2	MonoGuard	AY	2	80 µm / 0,186 ltr	Unnecessary						■	
Very High	110	2	MonoGuard	AY	2	110 µm / 0,256 ltr	Unnecessary							■
C3 - Low	75	1	MonoGuard	AY	1	75 µm / 0,174 ltr	Unnecessary				■			
Medium	90	2	MonoGuard	AY	2	90 µm / 0,209 ltr	Unnecessary					■		
High	110	2	MonoGuard	AY	2	110 µm / 0,256 ltr	Unnecessary						■	
Very High	150	2	MonoGuard	AY	2	150 µm / 0,349 ltr	Unnecessary							■
C4 - Low	100	2	MonoGuard	AY	2	100 µm / 0,233 ltr	Unnecessary				■			
Medium	125	2	MonoGuard	AY	2	125 µm / 0,291 ltr	Unnecessary					■		
High	150	2	MonoGuard	AY	2	150 µm / 0,349 ltr	Unnecessary						■	
Very High	200	2	MonoGuard	AY	2	200 µm / 0,465 ltr	Unnecessary							■
C5 - Low	150	2	MonoGuard	AY	2	150 µm / 0,349 ltr	Unnecessary				■			
Medium	175	2	MonoGuard	AY	2	175 µm / 0,407 ltr	Unnecessary					■		
High	200	2	MonoGuard	AY	2	200 µm / 0,465 ltr	Unnecessary						■	
Very High														■
Contact Acrymatic Coating for the right system in C5 - Very High														
AY: Acrylic paints.	MNOC: Minimum number of coats to get to NDFT.		gr. Gram.	ltr: Liter.										
NDFT: Nominal dry film thickness (Total amount of paint)			Stripe coat: Depends on the project.											



- Der tages forbehold for trykfejl / - Reservations are made for printing errors