

AC-MULTIPRIM

DESCRIPTION OF THE PRODUCT

USE:	Waterborne, indoor and outdoor, onecomponent universal primer. Based on acrylic polymers.
FEATURES:	Very good adhesion on most surfaces.
SUBSTRATES:	Galvanized steel, glass, zinc, hard PVC, steel...
SYSTEM:	<ul style="list-style-type: none">• Primer: 1 coat of AC-Multiprim.• Topcoat: Any waterbased, acrylic coating or 1 coat of AC-Multiprim.

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be cleaned, degreased and dry.
APPLICATION CONDITIONS:	Ambient temperature: > 5° C R.H.: max. 80 %
APPLICATION MEANS:	Brush or airless (nozzle: 011-015)
DILUTION:	Water
CLEANING OF TOOLS:	Water
CONSUMPTION:	Ca. 10m ² /L per coat
PARTICULARITIES:	Mix well before use

TECHNICAL DATA

FINISH:	Sati
COLOURS:	White
SOLIDS CONTENT:	In weight: ca. 54 % In volume: ca. 40 %
VOC CONTENT:	Max 40g/L
DENSITY:	Ca. 1,3
FLASH POINT:	Not flammable
VISCOSITY:	20-30 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 1 hour Recoatable: min. 4 hours
PACKING:	1 L – 2.5 L – 5L
STORAGE STABILITY:	12 months, kept in a frost free place

SAFETY DATA

The safety data sheet is available on request.

These directions are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.