

# AC-UniPrim

## DESCRIPTION OF THE PRODUCT

USE:	Waterborne onecomponent transparent impregnation primer, for porous and powdering supports, indoor and outdoor. To apply before a waterborne system. Based on acrylic resin dispersed in water.
FEATURES:	Good fixing capacity - The dispersed particles are very small, so it allows a better penetration of the substrate.
SUBSTRATES:	Porous substrates such as bricks, concrete, plaster and derivatives.
SYSTEM:	Primer: 1 impregnation coat of AC-UniPrim; Topcoat: 1 or 2 coats of a waterborne paint or a waterproofing product.

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry and free of dust
APPLICATION CONDITIONS:	Outdoor: never apply if raining Ambient temperature: > 5° C R.H.: max. 80 %
APPLICATION MEANS:	Brush, roller or airless (nozzle: 011-015)
DILUTION:	Don't dilute
CLEANING OF TOOLS:	Water
CONSUMPTION:	Ca. 10 m <sup>2</sup> /L in function of the porosity of the substrate
PARTICULARITIES:	Mix before use

## TECHNICAL DATA

FINISH:	The primer penetrates in the substrate and gives a glossy aspect
COLOURS:	Colourless
SOLIDS CONTENT:	In weight: ca. 15 % In volume: ca. 15 %
VOC CONTENT:	Max 0g/L
DENSITY:	Ca. 1.02
FLASH POINT:	Not flammable
VISCOSITY:	10 – 20 sec. (Ford 4 – 23°C)
DRYING TIME:	On touch: 1 hour Recoatable: 4 hours
PACKING:	1 L – 5 L – 20L
STORAGE STABILITY:	12 months in a frost free place

## SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.